



INSERT THE FOLLOWING TEXT IN THE OPTIONS AND MODIFICATIONS SECTION OF THE SPECIFICATIONS:

PYROCART SECONDARY HOSE CART WITH MANUAL REWIND REEL – ULTRA-HIGH PRESSURE

{Quantity} hose cart(s) with ultra-high pressure stainless steel hose reel shall be supplied. Each reel shall have leak proof ball bearing swing joint, positive pin locking device and plumbed with wire reinforced, ultra-high pressure hose coupled with brass fittings. The reel system shall have a minimum of 4:1 safety ratio and designed for a 2,000 PSI (135 bar) working pressure.

Each hose reel shall be trolley mounted and be rapid deployable with Ultra High Pressure quick connect couplings to allow for rapid extension of the hose reel lines.

The ultra-high pressure hose reel shall be supplied by 1/2" (12 mm) hydraulic type wire braided flexible hose line.

A chrome plated 3-way hose roller assembly shall be supplied on each cart for protection of the hose during hose removal and rewind operations.

REEL MOUNTED ULTRA-HIGH PRESSURE HOSE – (SECONDARY)

Each cart shall be equipped with 200' (60 m) x 3/4" (19 mm) hose installed with quick connect couplings. The hose shall have a working pressure of 3,125 psi (215 bar).