



**INSERT THE FOLLOWING TEXT IN THE OPTIONS AND MODIFICATIONS SECTION OF THE SPECIFICATIONS:**

**DELETE:**

**~~200' ELECTRIC REWIND HOSE REEL – ULTRA-HIGH PRESSURE~~**

~~One (1) painted ultra-high pressure steel hose reel shall be installed. The reel shall have a leak proof ball bearing swing joint, electric 12 volt rewind provisions. The reel system shall have a minimum of 4:1 safety ratio and designed for a 2,000 PSI (135 bar) working pressure.~~

~~Each reel {will/shall} be equipped with a locking pin assembly.~~

**REEL MOUNTED ULTRA-HIGH PRESSURE HOSE**

~~150 foot (45m) length x 3/4" (19mm) hose shall be installed with threaded couplings. The hose shall have a working pressure of 3125 psi (215bar).~~

**ADD:**

**300' ELECTRIC REWIND HOSE REEL – ULTRA-HIGH PRESSURE**

One (1) painted ultra-high pressure steel hose reel shall be installed. The reel shall have a leak proof ball bearing swing joint, electric 12 volt rewind provisions. The reel system shall have a minimum of 4:1 safety ratio and designed for a 2,000 PSI (135 bar) working pressure.

Each reel {will/shall} be equipped with a locking pin assembly.

**REEL MOUNTED ULTRA-HIGH PRESSURE HOSE**

300 foot (90m) length x 3/4" (19mm) hose shall be installed with threaded couplings. The hose shall have a working pressure of 3125 psi (215bar).